

## JM600 latex adhesive

A SOLVENT FREE natural rubber latex adhesive used as a general purpose carpet adhesive.

### USES

Its main use is for the permanent bonding of edges and seams of traditional carpets to prevent fibre loss. It is used with hessian seaming tape (Morley product code H5) for cold seaming of carpets. It can be used with jute hessian backed carpet for "repair" of permanent bonding to subfloor.

### SUBFLOORS

Subfloors must be sound, smooth, clean, dry and free from any contamination which will affect adhesion.

### PREPARATION

All parts of the installation should comply with the latest edition of BS 5325 The Installation of Textile Floorings. Another useful source of reference is The C F A Guide to Contract Flooring.

### APPLICATION

For best results a minimum temperature of 18°C (65°F) should be maintained for the installation.  
Edge Sealing:- apply the adhesive by brush or applicator to the edge of the carpet, having first removed any loose fibres. Allow the adhesive to fully dry before continuing with the installation.  
Seaming:- make sure both edges of the carpet are cleanly cut and

free from loose fibres; apply an even coat of JM600 to the back of the carpet and the seaming tape (Morley product code H5). Allow the adhesive to partially dry before pressing the two coated surfaces firmly together using a hand roller (Morley product code 10.100 Carpet Seamroller).

Caution: Do not stretch the carpet until the adhesive is completely dry. It could result in the seam opening up.

### HEALTH & SAFETY PRECAUTIONS

Refer to Material Safety Data Sheet and follow the advice given. Ensure area of use is well ventilated. Avoid prolonged contact with skin and if sensitive, use barrier cream or gloves. In case of contact with eyes, mouth or nose, rinse with plenty of water and seek medical help. If adhesive is spilled, remove and dispose of it in accordance with national and local regulations for waste materials.



### TECHNICAL SPECIFICATION

PRODUCT CODE - JM600

PRODUCT NAME - Latex Adhesive

CONTAINER SIZE - 5 ltr plastic jerry can

TYPE - Natural Rubber Latex

COLOUR - Off White

VISCOSITY - Approx. 6000 cps at 20°C - brush or applicator apply

COVERAGE - N/A

OPEN TIME - Approximately 20 minutes depending on temperature, humidity, sub floor porosity and trowel used.

STORAGE - Store between temperatures of 5°C and 30°C

SHELF LIFE - 12 months in unopened containers, stored in recommended conditions

CLEANING - Tools should be cleaned with water whilst the adhesive is wet. Use hot water or a solvent should the adhesive dry. Do not use on the skin.

*Health and Safety Sheets available on request.*

morleys limited   
*stairnosings & flooring accessories*

morleys limited, unit 2, higher walton mill,  
higher walton, preston pr5 4dj

tel. 01772 626700

fax. 01772 627372

e-mail. sales@morleysltd.co.uk

website. www.morleysltd.co.uk